

Puma AE (All Environment) is a fully waterproof, small, unmanned aircraft system (UAS) designed for land and maritime operations. Capable of landing in water or on land, the Puma AE empowers the operator with an operational flexibility never before available in the small UAS class. The enhanced precision navigation system with secondary GPS provides greater positional accuracy and reliability of the Puma AE. AV's common ground control system allows the operator to control the aircraft manually or program it for GPSbased autonomous navigation.





Downlink imagery from EO camera



SPECIFICATIONS

PAYLOADS	Gimbaled payload, 360 degree continuous pan, +10 to -90 degrees tilt, stabilized EO, IR camera, and IR Illuminator all in one modular payload.
RANGE	15 km
ENDURANCE	3+ hours
SPEED	37-83 km/h, 20 to 45 knots
OPERATING ALTITUDE (TYP.)	500 ft (152 m) AGL
WING SPAN	9.2 ft (2.8 m)
LENGTH	4.6 ft (1.4 m)
WEIGHT	14 lbs (6.3 kg)
GCS	Common GCS with Raven, Wasp and Shrike
LAUNCH METHOD	Hand-launched, rail launch (optional)
RECOVERY METHOD	Autonomous or manual deep-stall landing

KEY FEATURES

- 3+ Hour Flight Endurance
- Smart Battery options to support diverse missions
- Gimbaled EO & IR Payload
- Increased Payload Capacity with optional under wing Transit Bay
- Powerful and Efficient Propulsion System
- Precision Navigation System with Secondary GPS
- Plug and Play Secondary Power Adapter
- Reinforced Fuselage for Improved Durability



AeroVironment Corporate Headquarters – Simi Valley, CA 93065 USA – ph: 626.357.9983 – www.avinc.com © 2016 All product names copyright or trademark protected. All specifications are subject to change. This data sheet consists of AeroVironment, Inc. general capabilities information that does not contain controlled technical data as defined within the International Traffic in Arms (ITAR) Part 120.10 or Export Administration Regulations (EAR) Part 734.7-11.

