



telemax™ EVO PRO

The telemax EVO PRO's compact design with extended manipulator reach delivers proven performance in complex urban environments. Built for speed and mobility, its 4-track drive system, with optional snap on wheels for extra traction, enables it to easily traverse obstacles, gaps and steep inclines. Its 7-axis manipulator with Tool Center Point Control features a telescopic joint allowing for extended reach and precision operation in confined spaces. An expansive payload bay and automatic tool exchange allow operators to take multiple tools, disruptors or other sensors downrange, eliminating round-trip load-outs. Onboard IP Mesh radio delivers secure communications and the HD pan-tilt-zoom cameras produce razor-sharp images with four simultaneous video feeds (QuadView). All AeroVironment UGVs feature the intuitive and operationally simplified Robo Command Control Station with multi-touch screen, pre-programmed motion sequences and ergonomically designed hand controllers for precision control of the robot, manipulator and accessories.

Compact Design—Superior Mobility and Extended Reach

telexmax™ EVO PRO

DISTINCTIONS



» LIFTING CAPACITY

44 lb (20 kg)



» MANIPULATOR

7-axis with telescopic reach



» MISSION DURATION

Up to 10 hr



» CLIMB STAIRS AND SLOPES

45°

SPECIFICATIONS

TOTAL PAYLOAD CAPACITY	77 lb (35 kg)
SPEED	Max. 6.2 mph (10 km/h)
DIMENSIONS	31 in x 16 in x 29 in (775 mm x 400 mm x 750 mm)
WEIGHT	Max. 169 lb (77 kg)
DRIVE MECHANISM	4-track running gear with individually adjustable flippers; optional wheels
FUNCTIONALITY	Obstacle Height: 20 in (500 mm) Gap Width: 24 in (600 mm) Gripper Width: 4.7 in (120 mm) Reach Height: 150 in (2690 mm)

INTERCHANGEABLE ACCESSORIES



Optics/Visual
Augmentation



UGV
Communications



Power
Sources



Wheels/
Tracks



Tooling &
Hauling



Render Safe
Options

MISSION VARIANTS



EOD
Explosive Ordnance
Disposal



HAZMAT
Hazardous
Materials




CBRNE
Chemical, biological,
radiological, nuclear &
explosives



SWAT
High Risk Law
Enforcement
Operations


LIFT CAPACITY AT DISTANCE

6.6 lb (3 kg)	// 22 in (560 mm)
11 lb (5 kg)	// 31 in (800 mm)
27.5 lb (12.5 kg)	// 45 in (1140 mm)
44 lb (20 kg)	// 68 in (1730 mm)



ROBO COMMAND

Interoperable controller,
radio & communications—
reducing operation,
training & logistics



KEY FEATURES

- » 7-axis precision manipulator
- » Tool Center Point Control—providing maximum movement flexibility of the manipulator
- » Fully integrated 2-way audio module
- » HD pan-tilt-zoom cameras—displays four video feeds (QuadView)
- » Versatile 4-track drive system—handles gradients/obstacles/gaps
- » Easy access to pre-programmed manipulator & flipper motion sequences
- » IP Mesh Radio Network with optional repeaters provide secure & resilient communications over extended ranges